



CH horizontal plate lifting clamps

Product information



Lifting clamps for safe transportation of steel plates in horizontal position. For hoisting steel plates up to hardness 37 RC (345 HB).

Properties

- WLL and size of the jaw opening are clearly indicated on the clamp.
- Suitable for hoisting and horizontal transport of steel plates that do not bend.
- These clamps can also be applied under a lifting frame or chain sling.
- Always use in pair.
- Low weight and compact design.
- Safety factor of at least 5 x WLL.
- Each clamp is 2 x WLL testloaded.

Application

- For lifting steel plates up to hardness 37 RC (345 HB).
- For the safe transport of steel plates in horizontal position.

Marking: According to standard, CE-marked

Standard: EN 13155, EN 12100

Safety factor: 5

Part Code	GTIN No.	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	D mm	E mm	F mm	Weight kg/pair
3365001	8717365015786	1	0-35	CH-1.0	188	140	65	10	100	25	5.2/2
3365002	8717365015793	2	0-60	CH-2.0	290	180	90	15	115	31	15/2
3365102	8717365015847	2	0-100	CH-2.0/L	380	180	90	15	120	31	18/2
3365004	8717365015809	4	0-60	CH-4.0	306	220	105	25	145	31	26/2
3365104	8717365015854	4	0-100	CH-4.0/L	415	220	105	25	145	31	30/2
3365006	8717365015816	6	0-60	CH-6.0	306	220	110	25	145	31	26/2
3365106	8717365015861	6	0-100	CH-6.0/L	415	220	120	25	145	31	32/2
3365008	8717365015823	8	0-60	CH-8.0	335	225	120	35	135	31	36/2
3365108	8717365015878	8	0-100	CH-8.0/L	430	225	120	35	135	31	44/2
3365010	8717365015830	10	0-60	CH-10.0	335	225	120	35	135	31	40/2
3365110	8717365015885	10	0-100	CH-10.0/L	430	225	120	35	135	31	46/2

Blueprint

