

Portable swivel davit 125-250-500

Product information

Portable ergonomic modern design swivel davit for lifting.

Easily foldable, ready to use in a few seconds.

Integrated winch.

Including 8 meter wire rope (d5 mm) with hook

Specifications:

- Easy to transport, only 25 kg
- 360 degrees rotation over a built in ball bearing
- Maintenance free
- Adjustable crank
- The numbers in the product name correspond with the hoisting capacities on the first cable layer
- Beam reach differs from 60cm, 80cm to 100cm

Optional:

- zinc-plated finish (6 8 micron) (EV)
- stainless steel grade SAE 316 (SST316)
- ATEX certified (EX)

Accessories:

- floor, wall and in-cement floor sockets
- · carry bag and rain protection cover

Marking: According to standard, CE-marked

Standard: EN 13157

Safety factor: 4:1

Part Code	GTIN No.	WLL ton	Model	Rope Ø mm	Lift/crank turn (mm)	WLL Lifting 1st layer (kg)	Rope capacity m	Force on the handle (kg)	WLL Lifting outer layer (kg)	Weight kg
3750125	8717365187780	0.125	SD125	4	20	125	18	10	125	30
3750250	8717365187797	0.25	SD250	4	20	250	18	10	250	30
3750500	8717365187803	0.5	SD500	5	20	500	13	10	268	30

Blueprint

