



YAS lever hoist

Product information



The Rema® YAS lever hoist is an extremely robust lever hoist for pulling in all directions. With one simple action the lever hoist can be set in its freewheel.

Fitted with shipyard hooks.

Properties

- Grade 8 Galvanized load chain with high tensile strength.
- Compact construction and very low self-weight.
- Reliable self-locked brake which will retain the load at every required height.
- Hooks provided without safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Patented guide for the load chain.
- A double spring on each catch for additional safety.
- Equipped with shipyard hooks, only suitable for pulling.
- Can be used to pull steel sections together.

Standard delivery

- 1.5 m working length (maximum distance between top and bottom hook).

Option

- Longer chain length are available.

Marking: According to standard, CE-marked

Standard: EN 818-7

Part Code	GTIN No.	WLL kg	Lifting height m	Model	Load Chain dia x pitch mm	Max. hand force on crank kg	Chain falls	Construction height mm	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Weight kg
0208006-1.5	8717365104534	1,600	1.5	YAS-1600KG-SW	7,1 x 21	30	1	352	162	99	136	310	34	45	352	9.5
0208006-3	8717365104534	1,600	3	YAS-1600KG-SW	7,1 x 21	30	1	352	162	99	136	310	34	45	352	11.3
0208008-1.5	8717365104527	3,200	1.5	YAS-3200KG-SW	9,0 x 27,2	37	1	420	186.5	104	180	310	47	57	420	15.5
0208008-3	8717365104527	3,200	3	YAS-3200KG-SW	9,0 x 27,2	37	1	420	186.5	104	180	310	47	57	420	18.2

Blueprint

