



## BETA electric chain hoist

### Product information



The Rema® Beta 230 VAC electric chain hoists are light weight, compact and ideal for light installation work.

#### Properties

- Slip clutch for overload prevention
- Self-locking brake that will hold the load at any required height
- Very low own weight, only 7.5 kg.
- Very compact.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Grade 10 load chain.

#### Technical specification:

- Insulation class B.
- FEM 9.511 motor: 1Am.
- Power supply 230VAC.
- Protection class IP54
- Control power supply 230VAC direct control.

#### Standard delivery

- 3 m lifting height (maximum distance between top and bottom hook).
- 1.8 m control cable, direct control.
- 3 m power cable.
- Chain bag max 10 m.
- Trolley not included.

#### Option

- Other hoisting and operating height is also possible.
- Push trolley.

**Marking:** CE-marked

Part Code	GTIN No.	WLL kg	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Load Chain dia x pitch mm	Duty rating % ED	Construction height mm	Weight kg
0511001-3	8717365098758	125	3	6,5	1	BETA-125KG-3M	0.18	10	3 x 9	25	280	7.25
0511001-4	8717365118142	125	4	6,5	1	BETA-125KG-4M	0.18	10	3 x 9	25	280	8.5
0511001-5	8717365118159	125	5	6,5	1	BETA-125KG-5M	0.18	10	3 x 9	25	280	9.75
0511001-6	8717365118166	125	6	6,5	1	BETA-125KG-6M	0.18	10	3 x 9	25	280	11
0511001-7	8717365118173	125	7	6,5	1	BETA-125KG-7M	0.18	10	3 x 9	25	280	12.25
0511001-8	8717365118180	125	8	6,5	1	BETA-125KG-8M	0.18	10	3 x 9	25	280	13.5
0511001-9	8717365118197	125	9	6,5	1	BETA-125KG-9M	0.18	10	3 x 9	25	280	14.75
0511001-10	8717365118203	125	10	6,5	1	BETA-125KG-10M	0.18	10	3 x 9	25	280	16
0511003-3	8717365098765	200	3	3,8	1	BETA-200KG-3M	0.18	10	3 x 9	25	280	7.25
0511003-4	8717365118210	200	4	3,8	1	BETA-200KG-4M	0.18	10	3 x 9	25	280	8.5
0511003-5	8717365118227	200	5	3,8	1	BETA-200KG-5M	0.18	10	3 x 9	25	280	9.75
0511003-6	8717365118234	200	6	3,8	1	BETA-200KG-6M	0.18	10	3 x 9	25	280	11
0511003-7	8717365118241	200	7	3,8	1	BETA-200KG-7M	0.18	10	3 x 9	25	280	12.25
0511003-8	8717365118258	200	8	3,8	1	BETA-200KG-8M	0.18	10	3 x 9	25	280	13.5
0511003-9	8717365118265	200	9	3,8	1	BETA-200KG-9M	0.18	10	3 x 9	25	280	14.75
0511003-10	8717365118272	200	10	3,8	1	BETA-200KG-10M	0.18	10	3 x 9	25	280	16

# Blueprint

