



BETA electric chain hoist

Product information



The Rema® Beta 230 VAC electric chain hoists are light weight, compact and ideal for light installation work.

Properties

- Slip clutch for overload prevention
- Self-locking brake that will hold the load at any required height
- Very low own weight, only 7.5 kg.
- Very compact.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Grade 10 load chain.

Technical specification:

- Insulation class B.
- FEM 9.511 motor: 1Am.
- Power supply 230VAC.
- Protection class IP54
- Control power supply 230VAC direct control.

Standard delivery

- 3 m lifting height (maximum distance between top and bottom hook).
- 1.8 m control cable, direct control.
- 3 m power cable.
- Chain bag max 10 m.
- Trolley not included.

Option

- Other hoisting and operating height is also possible.
- Push trolley.

Marking: CE-marked

| Part Code | GTIN No. | WLL kg | Lifting height m | Lifting speed m/min | Number of falls | Model | Motor kW | Max. lifting height m | Load Chain dia x pitch mm | Duty rating % ED | Construction height mm | Weight kg | Delivery time |
|------------|---------------|-----------|---------------------|------------------------|-----------------|----------------|-------------|--------------------------|------------------------------|------------------|---------------------------|--------------|---------------|
| 0511001-3 | 8717365098758 | 125 | 3 | 6,5 | 1 | BETA-125KG-3M | 0.18 | 10 | 3 x 9 | 25 | 280 | 7.25 | 7 |
| 0511001-4 | 8717365118142 | 125 | 4 | 6,5 | 1 | BETA-125KG-4M | 0.18 | 10 | 3 x 9 | 25 | 280 | 8.5 | 7 |
| 0511001-5 | 8717365118159 | 125 | 5 | 6,5 | 1 | BETA-125KG-5M | 0.18 | 10 | 3 x 9 | 25 | 280 | 9.75 | 7 |
| 0511001-6 | 8717365118166 | 125 | 6 | 6,5 | 1 | BETA-125KG-6M | 0.18 | 10 | 3 x 9 | 25 | 280 | 11 | 7 |
| 0511001-7 | 8717365118173 | 125 | 7 | 6,5 | 1 | BETA-125KG-7M | 0.18 | 10 | 3 x 9 | 25 | 280 | 12.25 | 7 |
| 0511001-8 | 8717365118180 | 125 | 8 | 6,5 | 1 | BETA-125KG-8M | 0.18 | 10 | 3 x 9 | 25 | 280 | 13.5 | 7 |
| 0511001-9 | 8717365118197 | 125 | 9 | 6,5 | 1 | BETA-125KG-9M | 0.18 | 10 | 3 x 9 | 25 | 280 | 14.75 | 7 |
| 0511001-10 | 8717365118203 | 125 | 10 | 6,5 | 1 | BETA-125KG-10M | 0.18 | 10 | 3 x 9 | 25 | 280 | 16 | 7 |
| 0511003-3 | 8717365098765 | 200 | 3 | 3,8 | 1 | BETA-200KG-3M | 0.18 | 10 | 3 x 9 | 25 | 280 | 7.25 | 7 |
| 0511003-4 | 8717365118210 | 200 | 4 | 3,8 | 1 | BETA-200KG-4M | 0.18 | 10 | 3 x 9 | 25 | 280 | 8.5 | 7 |
| 0511003-5 | 8717365118227 | 200 | 5 | 3,8 | 1 | BETA-200KG-5M | 0.18 | 10 | 3 x 9 | 25 | 280 | 9.75 | 7 |
| 0511003-6 | 8717365118234 | 200 | 6 | 3,8 | 1 | BETA-200KG-6M | 0.18 | 10 | 3 x 9 | 25 | 280 | 11 | 7 |
| 0511003-7 | 8717365118241 | 200 | 7 | 3,8 | 1 | BETA-200KG-7M | 0.18 | 10 | 3 x 9 | 25 | 280 | 12.25 | 7 |
| 0511003-8 | 8717365118258 | 200 | 8 | 3,8 | 1 | BETA-200KG-8M | 0.18 | 10 | 3 x 9 | 25 | 280 | 13.5 | 7 |
| 0511003-9 | 8717365118265 | 200 | 9 | 3,8 | 1 | BETA-200KG-9M | 0.18 | 10 | 3 x 9 | 25 | 280 | 14.75 | 7 |
| 0511003-10 | 8717365118272 | 200 | 10 | 3,8 | 1 | BETA-200KG-10M | 0.18 | 10 | 3 x 9 | 25 | 280 | 16 | 7 |

Blueprint

