



EEFS elektric trolley 2 speed

Product information



EEFS 1-axle trolleys can ideally be combined with any electric chain hoist.

Properties

- 2 speed.
- Wheel rupture supports and anti-surge devices.
- Push-button box not included.

Technical properties

- Driving speed 5/20 m/min
- Operating voltage: 400V
- Control voltage: 24V
- Protection class: IP54
- Duty cycle 120 sw/h ED 40%
- isolation class: F
- Motor power 0.04/0.18 kW

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157, EN 1492-2

Note: Always specify flange width in mm.

Part Code	GTIN No.	WLL ton	Model	Minimum radius mm	A mm	B mm	F mm	G mm	H mm	J mm	K mm	N mm	R mm	S mm	U mm	Weight kg	Delivery time
0821001	8717365024238	1	EEFS10	1,000	28/32/35	26.5	66-300	24	71	70	122	356	109	140	104	22	7
0821003	8717365024245	2	EEFS20	1,500	35/40/45	26.5	66-300	24	87.5	70	122	356	135	140	104	25	3
0821005	8717365024252	3	EEFS32	2,000	45/50/55	28	82-300	32	93	103	122	356	156	140	141	40	7

Blueprint

