



Cordless remote control

Product information



REMA radio frequency system is a user-friendly, flexible and, first of all, a safe and ergono-mic way of remote control. It can be applied in the areas of industrial and building engineering.

Properties

- Range: appr. 1 meter.
- Led display, transmitter switched on.
- Functions: up/down/trolley drive.
- Several speeds can be facilitated.
- Transmitters are equipped with emergency stop class 3.
- Adjustable frequency (TM7).
- Class of protection IP 65.
- Ambient temperature -2°C to +65°C.
- Protection class IP65.
- Control voltage standard 24VAC

Standard delivery

- 1 transmitter included cord L-type.
- 1 receiver 24 VAC or 230 VAC.
- Included not-rechargeable batteries type AA for L-type.
- Tm70 included rechargeable battery and charger.

Option

- Several hoists can be controlled with a single hand-held transmitter (TM70).
- Crane bridge travelling.
- Other control voltages are available on request.

| Part Code | GTIN No. | Model | Dimensions Transmitter LxWxH mm | Dimension receiver LxWxH mm | Function | Number of speed | Weight kg | Delivery time |
|-----------|---------------|-------------------|------------------------------------|--------------------------------|--------------------------------|-----------------|--------------|---------------|
| 0725700 | 8717365001819 | 1-L4 | 163 x 49 x 45 | 161 x 74 x 52 | up/down | 1 | 0.15 | 7 |
| 0725702 | 8717365001826 | 1-L6 | 163 x 49 x 45 | 161 x 74 x 52 | up/down/left/right | 1 | 0.15 | 3 |
| 0725706 | 8717365001833 | 1-L6B | 163 x 49 x 45 | 167 x 154 x 88 | up/down/left/right | 2 | 0.28 | 7 |
| 0725500 | 8717365001802 | TM70/1.13 | 215 x 70 x 52 | 285 x 200 x 110 | up/down/left/right/crane drive | 2 | 0.46 | 7 |
| 0725300 | 8717365261541 | TM70/1.06 HYBRIDE | 160 x 75 x 45 | 151 x 129 x 61 | up/down/left/right | 2 | 0.64 | 7 |