



BLACK-LINE hand chain hoist

Product information



The Rema® BLACKLINE hand chain hoist is suitable for theater purposes where safety, ergonomics and a low operating force are paramount. The body and hooks are coloured black to limit visibility in sensitive dark environments.

Properties

- Low operating effort at full load.
- Increased operational safety due to double pawl system.
- Load pressure brake with asbestos free friction discs.
- Load chain wheel is made of wear-resistant alloy steel.
- Top and bottom hook have safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain (Grade 8).
- Galvanized hand chain.

Standard delivery

- Lifting height 10 or 15 meters

Option

- Other lifting heights on request.
- Chain bucket for load chain up to 10 meters lifting height.

Norm:

- EN12100-1/2, EN13157, EN818-7



Marking: According to standard, CE-marked

Standard: EN 13157, EN 818-7

Part code	GTIN No.	WLL	Lifting height kg m	Model	Load Chain dia x pitch mm	Hand Chain Ø x pitch mm	Chain falls	Construction height mm	Hand force max. kg	A	B	C	D	H	Weight kg	Delivery time
0171000-108717365149962	250	10	X-LINE/250KG/BLACK-10M	4.0 x 12	5.0 x 23.7	1	280	23.5	108	106	20	30	280	6	7	
0171000-158717365149979	250	15	X-LINE/250KG/BLACK-15M	4.0 x 12	5.0 x 23.7	1	280	23.5	108	106	20	30	280	6	7	
0171001-108717365149986	500	10	X-LINE/500KG/BLACK-10M	5.0 x 15	5.0 x 23.7	2	280	24.9	130	128	22	34	280	9	7	
0171001-158717365149993	500	15	X-LINE/500KG/BLACK-15M	5.0 x 15	5.0 x 23.7	2	280	24.9	130	128	22	34	280	9	7	

Blueprint

