



Load binders

Product information



Load binders are used for the safe securing of heavy loads by road, rail, air and ship transport. The lashing chains are equipped with a ratchet tensioner, load hooks with safety latches, shortening claw with a safety device that prevents the chain from vibrating during transport. The ratchet tensioner applies a force to the chains in a controlled manner.

Properties

- Ratchet tensioner with secure-locking.
- Long side can be shortened safely by the shortening claw.
- Safety label with workload and tension force.
- Chains and accessories Grade 10, tensioner Grade 8
- Standard working length 3.5 m.
- Length of crank 355 mm.

IMPORTANT:

- Every load, independent of its weight, must be secured.
- Load binders are not suitable for lifting a load.
- Never extend the handle with a pipe for more force.
- Never subject chains, hooks and tensioner over sharp edges.
- Use corner protectors or guides on sharp edges (r radius $<$ diameter chain).
- Lashing chain with stretched or bent links, cracks, etc. may no longer be used.
- In case of doubt, always have it inspected and / or repaired by authorized persons or authorities.

Marking: According to standard

Standard: EN 12195-3

| Part Code | GTIN No. | Diameter mm | LC daN | Length | Model | STF daN | Weight | Delivery time |
|-----------|---------------|-------------|--------|--------|---------------|---------|--------|---------------|
| 3025108 | 8717365175886 | 8 | 5,000 | 3.5 | TLB-8mm-3,5m | 1,900 | 12 | 7 |
| 3025110 | 8717365175893 | 10 | 8,000 | 3.5 | TLB-10mm-3,5m | 1,900 | 19 | 7 |
| 3025113 | 8717365175909 | 13 | 13,400 | 3.5 | TLB-13mm-3,5m | 2,500 | 33 | 7 |