



## C807X+KEY lifting points (Grade 10)

### Product information



**Features:** Tighten hand-tight in load direction.

**Marking:** According to standard, CE-marked

**Standard:** EN 1677-1

**Note:** Rotatable through 360°

**Warning:** Not rotatable under load.

**Safety factor:** 4

**Grade:** 10

Part Code	GTIN No.	WLL ton	Thread mm	Model	A mm	B mm	C mm	D mm	E mm	F mm	K mm	M x L mm	SWI mm	Weight kg	Delivery time
2611408	8717365116018	0.3	M8	C807X+KEY-M8x12-0.3T	35	11	9	25	25	30	47	M8 x 12	6	0.12	3
2611410	8717365116025	0.4	M10	C807X+KEY-M10x15-0.4T	35	11	9	25	25	30	47	M10 x 16	6	0.12	3
2611412	8717365116032	0.75	M12	C807X+KEY-M12x23-0.75T	43	12,5	11,5	30	30	36,5	55,5	M12 x 18	7	0.2	3
2611416	8717365116049	1.5	M16	C807X+KEY-M16x24-1.5T	49,5	14,5	15,7	35	35	41,8	64,5	M16 x 24	8	0.35	3
2611420	8717365116056	2.3	M20	C807X+KEY-M20x30-2.3T	58	16	18	40	42	51,5	74,5	M20 x 30	10	6	7
2611424	8717365116063	3.2	M24	C807X+KEY-M24x36-3.2T	69	20,5	22	49	50	58	90	M24 x 36	12	1	3
2611430	8717365116070	4.5	M30	C807X+KEY-M30x45-4.5T	86	25,5	28	60	66	73	111	M30 x 43	17	2	3
2611436	8717365116087	7	M36	C807X+KEY-M36x54-7.0T	107	32	32	74	75	96,5	135	M36 x 54	22	2	7
2611442	8717365116094	9	M42	C807X+KEY-M42x63-9.0T	120	38	40,5	82	85	110	158	M42 x 64	24	5.7	7
2611448	8717365116100	12	M48	C807X+KEY-M48x72-12T	139	43	44	95	100	124,5	179	M48 x 72	27	8.5	7

# Blueprint

