



Eye-bolt (DIN-580)

Product information



High-alloyed steel eyebolt. Eye bolts may only be tightened by hand.
Safe workload, under a maximum angle of 60° as shown.
The lifting eye must not be loaded sideways.

Marking: According to standard, CE-marked
Standard: EN 1677-1, DIN 580

Safety factor: 4
Grade: 8

| Part code | GTIN No. | WLL ton | Thread mm | Model | A mm | B mm | C mm | D mm | M mm | Weight kg | Delivery time |
|-----------|---------------|---------|-----------|---------------|------|------|------|------|------------|-----------|---------------|
| 2675308 | 8717365115202 | 0.4 | M8 | DIN580-G8-M8 | 34 | 7 | 20 | 13 | M8 x 1,25 | 0.05 | 3 |
| 2675310 | 8717365115219 | 0.7 | M10 | DIN580-G8-M10 | 38 | 8 | 22 | 17 | M10 x 1,50 | 0.07 | 3 |
| 2675312 | 8717365115226 | 1 | M12 | DIN580-G8-M12 | 47 | 10 | 26 | 21 | M12 x 1.75 | 0.13 | 3 |
| 2675316 | 8717365115233 | 1.5 | M16 | DIN580-G8-M16 | 64 | 14 | 35 | 27 | M16 x 2.00 | 0.34 | 3 |
| 2675320 | 8717365115240 | 2.5 | M20 | DIN580-G8-M20 | 73 | 16 | 39 | 30 | M20 x 2.50 | 0.52 | 3 |
| 2675324 | 8717365115257 | 4 | M24 | DIN580-G8-M24 | 95 | 20 | 54 | 36 | M24 x 3.00 | 0.99 | 3 |