

CHTV horizontal lifting clamps with spring



Product information



REMA CHTV horizontal clamps are fitted with a torsion spring so that the lifting clamp remains closed at the desired location. 1 person can place 4 clamps and operate the crane.

Application

- 1 person can place 4 clamps and operate the crane.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13155

Safety factor: 5

| Part Code | GTIN No. | WLL ton | Jaw width mm | Model | A mm | B mm | C mm | D mm | E mm | F mm | G mm | Weight kg/pair | Delivery time |
|-----------|---------------|---------|--------------|--------|------|------|------|------|------|------|------|----------------|---------------|
| 3369001 | 8717365259166 | 1 | 0-35 | CHTV-1 | 193 | 140 | 85 | 10 | 100 | 25 | 15 | 6/2 | 3 |
| 3369002 | 8717365259173 | 2 | 0-60 | CHTV-2 | 290 | 180 | 125 | 15 | 115 | 30.5 | 16 | 18/2 | 3 |
| 3369003 | 8717365259180 | 3 | 0-60 | CHTV-3 | 293 | 180 | 125 | 20 | 115 | 30.5 | 16 | 20/2 | 3 |
| 3369004 | 8717365261831 | 4 | 0-60 | CHTV-4 | 310 | 220 | 165 | 30 | 140 | 30.5 | 20 | 30/2 | 7 |
| 3369006 | 8717365261848 | 6 | 0-60 | CHTV-6 | 310 | 220 | 165 | 30 | 140 | 30.5 | 20 | 30/2 | 7 |

Blueprint

