



CNM non-marking vertical plate lifting clamps

Product information



The CNM clamp is equipped with 2 clamping jaws that are provided with special synthetic plastic. After hoisting, the clamp leaves no damage. The clamp is locked in the closed and open position.

Properties

- Equipped with synthetic plastic jaws.

Application

- For hoisting and transporting of, stainless steel, aluminum, wood and natural stone where the workpiece can not be damaged.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13155

Part Code	GTIN No.	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg	Delivery time
3315001	8717365015373	0.5	1-20	CNM-0.5	102	65	462	224	48	80	48	6	3
3315003	8717365015397	0.5	17-37	CNM-0.5G	102	65	462	241	48	80	48	6	3
3315000	8717365015366	1	1-30	CNM-1.0	105	80	470	282	57	80	54	6.5	3
3315002	8717365015380	1.5	1-40	CNM-1.5	105	80	470	282	57	80	54	6.5	3
3315004	8717365015403	2	1-50	CNM-2.0	124	100	704	408	63	80	65	15	3
3315005	8717365015410	3	1-60	CNM-3.0	124	100	704	408	63	80	65	15.5	3

Blueprint

