



CS vertical plate lifting clamps

Product information



Lifting clamps for safely transporting steel plates in vertical position.

Properties

- Equipped with standard lifting eye, movable in one direction.
- Always equipped with a safety mechanism, ensuring the clamp does not slip when lifting force is applied and when load is being lowered.
- WLL and size of the jaw opening are clearly indicated on the clamp.
- Safety factor of at least 5 x WLL.
- Each clamp is 2x WLL testloaded.

Application

- For lifting steel plates up to a hardness of 37 RC (345 HB).
- Suitable for lifting, 180 ° turning and vertical transport of steel plates.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13155

Note: Minimum weight to be lifted is 10% of the safe workload.

Safety factor: 5

Part Code	GTIN No.	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg	Delivery time
3360001	8717365015595	0.75	0-13	CS-0.75	47	30	205	100	35	37	10	1.5	7
3360002	8717365261862	1	0-25	CSE-1.0	55	45	265	142	38	47	15	3.6	7
3361002	8717365015625	2	0-35	CS-2.0	80	65	335	185	55	56	17	6.5	3
3361003	8717365015632	3	0-35	CS-3.0	80	65	335	185	55	56	17	7	3
3361004	8717365015649	4	0-45	CS-4.0	85	70	430	230	60	78	20	16	3
3361006	8717365015656	6	0-50	CS-6.0	114	75	490	255	78	78	20	20	7
3361009	8717365015663	9	0-55	CS-9.0	112	75	530	267	70	86	20	26	3
3361013	8717365015670	12	0-52	CS-12.0	148	85	617	295	100	94	44	42	3
3361015	8717365015687	15	0-75	CS-15.0	159	86	760	375	135	105	50	71	7

Blueprint

