



Weber A and AT hydraulic jacks

Product information



Properties

- Type A has a piston with screw spindle so that the minimum height can easily be adjusted.
- Type AT has 2 pistons so that a greater lift height is achieved.
- Protection against overload by overpressure valve.
- A carrying handle is supplied from a weight of 10 kg.
- The spherical foot (*) reduces the lateral pressure.
- Can be used from -20? up to +70? C.
- Not suitable for continuous supporting the load.
- Suitable for horizontal use up to A-30, provided that pump part is at the bottom.

Marking: According to standard, CE-marked

Standard: EN 12100, DIN 76024, EN 1494

Part Code	GTIN No.	WLL ton	Model	A mm	B mm	C mm	D mm	E mm	F mm	Weight kg	Delivery time
2705001	8717365012891	2	A2-170	170	92	115	377	28	103 x 105	2.9	3
2707001	8717365013027	3	ATDX3-185*	185	-	215	400	R50	126 x 93	4.2	3
2705003	8717365012907	3.5	A3.5-170	170	92	115	377	28	103 x 105	2.9	3
2705005	8717365012914	5	A5-212	212	100	150	462	40	110 x 110	3.9	3
2707003	8717365013041	5	AT5-215*	215	-	305	520	43	134 x 120	6.3	3
2705007	8717365012921	8	AX8-220*	220	110	150	480	48	124 x 122	5.7	3
2705009	8717365012938	10	A10-220*	220	110	150	480	48	124 x 122	5.7	3
2707007	8717365013058	10	ATG10-200*	200	68	262	530	43	164 x 160	8.8	3
2705011	8717365012945	12	A12-230*	230	110	157	497	48	134 x 120	7.1	3
2707009	8717365013072	12	ATPX12-230	230	85	255	570	48	176 x 185	12.2	3
2705013	8717365012952	15	AX15-230*	230	110	155	495	60	139,5 x 130	8.3	3
2705015	8717365012969	20	AX20-240*	240	110	155	505	60	164 x 160	10.7	3
2705017	8717365012976	25	AH25-240*	240	118	157	515	65	185 x 176	13.1	3
2705019	8717365012983	30	A30-240*	240	100	142	482	65	185 x 176	14.5	3
2705021	8717365012990	50	A50-250	250	-	155	405	72	290 x 235	33	7
2705023	8717365013003	100	AX100-300	300	-	150	450	95	330 x 295	87	7

Blueprint

