

Hoist traverse beam REMA , with 2 fixed hooks.



Product information



Properties

- Surface finish: zinc phosphate primer RAL 2004 (orange).
- Capacity range labelling.
- Black-and-yellow safety markings at beam ends.
- Hooks equipped with safety latches.
- High quality steel hooks grade 10.

Option

- Sandblasting and painting in every RAL color.
- Higher load capacity and bigger dimensions on request.

Marking: According to standard, CE-marked

Standard: EN 13155, EN 12100, EN 1677-1

Part code	GTIN No.	WLL ton	Model	A mm	B1 mm	C mm	D mm	H mm	L mm	Weight kg	Delivery time
3962001	8717365017728	1	TRA-VA-1000-1M	1,070	65	85	55	380	1,000	13	7
3962003	8717365017735	1	TRA-VA-1000-1.6M	1,670	65	85	55	400	1,600	22	3
3962005	8717365017742	1	TRA-VA-1000-2.5M	2,570	75	85	55	420	2,500	38	7
3962007	8717365017759	1	TRA-VA-1000-3,15M	3,220	85	85	55	420	3,150	57	7
3962009	8717365017766	1.6	TRA-VA-1600-1,6M	1,690	75	85	55	480	1,600	27	7
3962011	8717365017773	1.6	TRA-VA-1600-2,5M	2,590	85	85	55	500	2,500	55	7
3962013	8717365017780	1.6	TRA-VA-1600-3,15M	3,240	90	85	55	520	3,150	78	7
3962015	8717365017797	1.6	TRA-VA-1600-4M	4,090	100	85	55	520	4,000	98	7
3962017	8717365017803	2.5	TRA-VA-2500-2,5M	2,590	90	85	70	540	2,500	68	7
3962019	8717365017810	2.5	TRA-VA-2500-3,15M	3,240	100	85	70	560	3,150	111	7
3962021	8717365017827	2.5	TRA-VA-2500-4M	4,090	110	85	70	580	4,000	138	7
3962023	8717365017834	2.5	TRA-VA-2500-5M	5,090	135	85	70	600	5,000	198	7

Blueprint

