



## HSL low profile lifting tables

### Product information



For lifting heavy loads in the simplest possible way, then the low stationary lifting table with the practical ramps offers a solution. The extremely low lifting table prevents time-consuming construction efforts for the creation of a pit. The practical ramp provides a solution for getting on and off with a pallet truck or transport trolley.

#### Properties

- Stable low bottom plate.
- Solid steel scissors.
- This lifting table is equipped with an aluminium safety frame.
- Support inspection for safe maintenance.
- Overload protection.
- Hose rupture safety valve.
- Hard chromed cylinder and piston rod.
- Lifetime lubricated bearings.
- External drive unit.
- The inclination angle of the ramp is 5 °.
- Operating voltage 400V, control voltage 24V.
- Protection class IP54.

#### Standard delivery

- Includes 24 V remote unit with push buttons with emergency stop.
- Removable lifting eyes for easy transport.
- Ramp.

**Marking:** According to standard, CE-marked

**Standard:** EN 13157, EN 12100

Part Code	GTIN No.	WLL ton	Model	Lifting times	Motor power kW	Lifting cycle/hour	A mm	B mm	C mm	D mm	E mm	H mm	Weight kg
3459011	8717365016288	1	HSL-1.0	20	0,75	21	85	1,600	1,140	1,074	1,325	860	302
3459015	8717365016301	2	HSL-2.0	20	2,2	15	105	1,600	1,200	1,114	1,427	870	390

## Blueprint

