



## Manually operated mobile lifting table

### Product information



The ergonomic solution for bringing parts and tools to work height when working on machines.

Type HT: hand-operated lifting table.

Type D: double scissors for even more lift height.

#### Properties

- Hydraulic system provides for a higher level of safety.
- Foot pedal for lifting.
- Controllable descent rate by means of control lever.
- REMA movable lifting tables are fitted with two fixed wheels and two steer wheels with brake.
- HT-15 is equipped with foldable push handle, other types have fixed push handle.

**Marking:** According to standard, CE-marked

**Standard:** EN 1570, EN 12100

Part Code	GTIN No.	WLL ton	Model	Wheels diameter mm	Platform size mm	Min height mm	Max. lifting height mm	Weight kg	Delivery time
3460015	8717365000355	0.15	HT-15	100	700 x 450	260	765	41	3
3460025	8717365000362	0.25	HT-25	125	815 x 500	310	910	78	3
3460050	8717365000379	0.5	HT-50	150	1010 x 520	420	1,010	118	3
3460150	8717365016349	0.5	HT-50D	150	1010 x 520	435	1,585	168	7
3460075	8717365000386	0.75	HT-75	150	1010 x 520	420	1,010	120	7
3460100	8717365000393	1	HT-100	150	1010 x 520	430	955	145	7