



HSU low profile lifting table

Product information



For lifting heavy loads in the simplest possible way, then the low U stationary lifting table offers a solution because this table has a recess where a pallet truck can be placed. The extremely low lifting table prevents time-consuming construction efforts for the creation of a pit.

Properties

- Stable low bottom plate.
- Solid steel scissors.
- This lifting table is equipped with an aluminium safety frame.
- Support inspection for safe maintenance.
- Overload protection.
- Hose rupture safety valve.
- Hard chromed cylinder and piston rod.
- Lifetime lubricated bearings.
- External drive unit.
- Operating voltage 400V, control voltage 24V.
- Protection class IP54.

Standard delivery

- Incl 24 V remote control buttons and emergency stop.
- Demountable lifting eyes for easy transport.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157

Part Code	GTIN No.	WLL ton	Model	Lifting times	Motor power kW	Lifting cycle/hour	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg
3459017	8717365016318	1	HSU-1.0	18	0,75	20	85	1,450	1,140	1,074	1,325	585	1,080	860	280
3459019	8717365016325	1.5	HSU-1.5	18	1,5	20	105	1,600	1,180	1,114	1,427	585	1,194	860	380

Blueprint

