



DLB brake winch

Product information



Properties

- Zinc-plated housing (DL2500G has a ungalvanized drum).
- Fitted with automatic load pressure brakes.
- For extra safety, they are fitted with locking pawls.

Standard delivery

- Does not include cable.

Options

- Steel wire rope according DIN 3060 with safety hook.
- Sling belt according DIN 3060 with safety hook.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157

Warning: For lifting, select another wire rope diameter, taking tensile strength into consideration. Minimum load required for winch to operate properly.

Part Code	GTIN No.	WLL ton	Model	Cable Diameter mm	Lift/crank turn (mm)	Gear ratio	Max. reel capacity mm	Force on the handle (kg)	Drum mm	Length handle mm	Weight kg	Delivery time
2117010	8717365110580	0.159	DLB-350A	3	22.5	3.2 :1	25	10	26 x 52	178	3	7
2117011	8717365008979	0.36	DLB-800AG	4	36	4.4 :1	23	12	48 x 53	178	3	7
2117013	8717365008986	0.545	DLB-1200AG	5	39	5.4 :1	19.7	19	64 x 51	238	4	7
2117015	8717365008993	0.68	DLB-1500AG	6	40	5.4:1	15.1	18	64 x 62	305	5	7
2117016	8717365009006	0.905	DLB-2000AG	7	30	17.3 :1	8.9	8	64 x 54	238	7	7
2117017	8717365009013	1.135	DLB-2500G	8	23	12.0 :1	7.4	13	79 x 66	244	12	7

Blueprint

