



RGL gear winches

Product information



Properties

- Construction according to DIN 152.
- Braked design with double pawl system.
- Crank gradually adjustable in length.
- Drum and shafts provided with bearings.
- Freewheel, through protected pawl system.
- Powdercoating RAL 2004.

Standard delivery

- Does not include wire rope.

Option

- Steel wire rope on request with hook and safety latch.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157

Part Code	GTIN No.	WLL ton	Model	Cable Diameter mm	Gear ratio	Max. reel capacity mm	Length handle mm	Load capacity last layer kg	load capacity 1st layer kg	Weight kg	Delivery time
2017001	8717365259265	0.15	RGL-150	4	2.84 :1	22	250/100	45	150	9.2	3
2017003	8717365259272	0.3	RGL-300	5	6.67:1	30	250/100	100	300	16.5	3
2017005	8717365259289	0.5	RGL-500	6	7.75 :1	30	250/100	300	500	18.5	7

Technical data

Model	A	B	C	D	F	G	H	J	K	L	M	N	P	Q	R	S	T	U	V	
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
RGL-150	180	324	150	150	154															

Blueprint

