



## WW worm gear winches

### Product information



#### Properties

- Load pressure brake.
- Adjustable crank length; backwind-free.
- Drums and axes run on needle bearings.
- Models above load capacity of 2 kg have two speeds, which is operated by changing the crank over.
- Paint finish and enamel varnish are standard.

#### Standard delivery

- Does not include wire rope.

#### Option

- Steel wire rope on request.

**Marking:** According to standard, CE-marked


**Standard:** EN 13157, EN 12100

| Part Code | GTIN No.      | WLL ton | Model   | Cable Diameter mm | Lift/crank turn (mm) | Max. reel capacity mm | Force on the handle (kg) | Load capacity last layer kg | load capacity 1st layer kg | Weight kg | Delivery time |
|-----------|---------------|---------|---------|-------------------|----------------------|-----------------------|--------------------------|-----------------------------|----------------------------|-----------|---------------|
| 2016001   | 8717365008771 | 0.25    | WW-250  | 4                 | 17                   | 104                   | 3.5                      | 95                          | 250                        | 13        | 3             |
| 2016003   | 8717365008788 | 0.5     | WW-500  | 6                 | 20                   | 78                    | 9                        | 239                         | 500                        | 16        | 3             |
| 2016005   | 8717365008795 | 1       | WW-1000 | 8                 | 13                   | 63                    | 15.5                     | 542                         | 1,000                      | 26        | 3             |
| 2016007   | 8717365008801 | 1.5     | WW-1500 | 10                | 9                    | 41                    | 19                       | 845                         | 1,500                      | 28        | 3             |
| 2016009   | 8717365008818 | 2       | WW-2000 | 12                | 12/6                 | 46                    | 22/13                    | 1,129                       | 2,000                      | 60        | 3             |
| 2016011   | 8717365008825 | 3       | WW-3000 | 14                | 11/6                 | 52                    | 27/14                    | 1,861                       | 3,000                      | 78        | 7             |
| 2016012   | 8717365024269 | 4       | WW-4000 | 16                | 11/4                 | 52                    | 35/13                    | 2,390                       | 4,000                      | 80        | 7             |
| 2016013   | 8717365008849 | 5       | WW-5000 | 18                | 12/4                 | 40                    | 58/17                    | 3,165                       | 5,000                      | 115       | 7             |


## Technical data

| Type   | A   | B   | C   | D   | G   | H   | J  | K  | L   | M   | N  | O   | P   | R   | S   |
|--------|-----|-----|-----|-----|-----|-----|----|----|-----|-----|----|-----|-----|-----|-----|
| WW-250 | 238 | 145 | 100 | 192 | 106 | 102 | 48 | 14 | 160 | 191 | 15 | 410 | 280 | 171 | 130 |
| WW-500 | 269 | 160 | 115 | 223 | 107 | 131 | 70 | 14 | 190 | 221 | 15 | 440 | 325 |     |     |

# Blueprint



WW-250 - WW-1500



WW-200 - WW-500