



P25 Pallet truck

Product information

With the P25, REMA offers a reliable quality pallet truck. The comfortable operating handle controls lifting, driving and lowering. Controlled lowering is also easy with the foot pedal on the hydraulic pump. The large, low-noise polyurethane steering wheels and tandem rollers ensure that the pallet truck is easy to maneuver and remains smooth on uneven floors. The P25 is also equipped with in and out rollers with which you can easily drive in and out of the pallet. The sturdy steel frame has an orange powder coating.

Properties

- Pump unit equipped with overload protection
- Steel frame with orange powder coating
- Foot pedal for controlled lowering of the load
- Equipped with in and out rollers

Technical specifications

- Highest position forks 200 mm
- Steering wheel diameter 200 mm (Polyurethane)
- Diameter fork rollers 85 mm (Polyurethane)
- Width over the forks 540 mm
- Fork length 1150 mm
- Fork width 160 mm

Marking: CE-marked

Part Code	GTIN No.	WLL ton	Model	Width of forks mm	Minimum height of fork mm	Version of fork roller	Material fork wheel	Material steering wheel	Dimensions mm	Colour	Weight kg
3402101	8717365184956	2.5	P25-2500KG-PPT	160	85	Tandem	Polyurethan	Polyurethan	1150 x 540	Orange	70