



## CPH pipe lifting hooks

### Product information



#### Properties

- Jaw is covered with a special high quality pressure resistant plastic.
- These hooks must always be used in pairs.

#### Application

- For horizontal lifting and transporting of steel and concrete pipes without damaging the product.

**Marking:** According to standard, CE-marked

**Standard:** EN 13155, EN 12100

| Part Code | GTIN No.      | WLL ton | Jaw width mm | Model    | A mm | B mm | C mm | D mm | E mm | F mm | O mm | X mm | Weight kg/pair |
|-----------|---------------|---------|--------------|----------|------|------|------|------|------|------|------|------|----------------|
| 3313025   | 8717365015304 | 1,5     | 40           | CPH-1.5  | 120  | 32   | 185  | 70   | 41   | 16   | 40   | 23   | 3,2            |
| 3313027   | 8717365015311 | 3       | 40           | CPH-3.0  | 120  | 32   | 185  | 70   | 41   | 16   | 40   | 23   | 3,2            |
| 3313029   | 8717365015328 | 4       | 50           | CPH-4.0  | 140  | 58   | 180  | 70   | 41   | 26   | 50   | 23   | 6              |
| 3313031   | 8717365015335 | 6       | 50           | CPH-6.0  | 140  | 58   | 180  | 70   | 41   | 26   | 50   | 23   | 6              |
| 3313033   | 8717365015342 | 8       | 70           | CPH-8.0  | 140  | 58   | 200  | 70   | 45   | 26   | 70   | 25   | 7,2            |
| 3313034   | 8717365023590 | 10      | 70           | CPH-10.0 | 140  | 58   | 200  | 70   | 86   | 26   | 70   | 44   | 10             |
| 3313035   | 8717365258725 | 12      | 70           | CPH-12.0 | 140  | 58   | 200  | 70   | 86   | 26   | 70   | 44   | 12             |
| 3313037   | 8717365258732 | 15      | 70           | CPH-15.0 | 155  | 75   | 250  | 70   | 100  | 26   | 70   | 59   | 18             |
| 3313039   | 8717365258749 | 20      | 70           | CPH-20.0 | 155  | 75   | 250  | 70   | 100  | 26   | 70   | 59   | 20             |

## Blueprint

