



C806X-aanslagbout (G10)

Productinformatie



Markering: Volgens norm, CE

Norm: EN 1677-1

Opmerking: 360° draaibaar, 90° opklapbaar en belastbaar.

Waarschuwing: Niet draaibaar onder last.

Veiligheidsfactor: 4

Artikelnr.	GTIN Nr	WLL ton	Draad mm	Type	A mm	B mm	C mm	D mm	E mm	G mm	K mm	M mm	L mm	SW mm	Gewicht
2611208	8717365176029	0,3	M8	C806X-M8x15-0.3T	34	57	24	10	43	78	25	M8	15	13	0,28
2611212	8717365176043	1	M12	C806X-M12x23-1.0T	38	66	30	13,5	40	85	32	M12	23	19	0,5
2611216	8717365176050	1,5	M16	C806X-M16x24-1.5T	38	66	30	13,5	38	85	32	M16	24	24	0,51
2611220	8717365176067	2,5	M20	C806X-M20x31-2.5T	55	87	48	16	54	111	45	M20	31	30	1,25
2611224	8717365176074	4	M24	C806X-M24x37-4.0T	55	87	48	16	51	111	45	M24	37	36	1,3
2611230	8717365176081	5	M30	C806X-M30x45-5.0T	66	109	54	22,5	62	145	60	M30	45	46	3,25
2611236	8717365176098	7	M36	C806X-M36x50-7.0T	66	109	54	22,5	60	145	60	M36	50	55	3,3
2611242	8717365176104	10	M42	C806X-M42x75-10T	78	136	62	28	86	190	70	M42	75	65	11,2
2611243	8717365176111	15	M42	C806X-M42x63-15T	97	169	68	36	121	242	85	M42	63	65	6,5
2611248	8717365176128	20	M48	C806X-M48x71-20T	97	169	68	36	117	242	95	M48	71	75	11,6
2611210	8717365176036	63	M10	C806X-M10x15-0.63T	34	57	24	10	42	78	25	M10	15	17	0,29

Maattekening

