



H-100 hand chain hoist

Product information



Model Rema[®] H-100 is a robust hand chain hoist designed for heavy and increased loads, bearing safety, ergonomics and low operating effort in mind.

Properties

- Low operating effort at full load due to bearing shafts.
- Double brake pawl system.
- Self-locking brake that can hold loads at any desired height.
- Suspension and load hooks equipped with safety latches.
- The load hook will yield under overload instead of breaking.
- Zinc-plated load chain (grade 8 in compliance with EN 818-7).
- Zinc plated hand chain.
- Reliable steel plate housing in orange finish.

Standard delivery

- 3 m hoisting height.
- 2,5 m operating height.

Option

- Available in any other hoisting and operational heights.

Marking: According to standard, CE-marked

Standard: EN 13157, EN 818-7

Part Code	GTIN No.	WLL	Lifting height ton m	Model	Load Chain dia x pitch mm	Hand Chain Ø x pitch mm	Chain falls	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	Weight kg
0100001-3	8717365264191	0,5	3	H100-500KG-3m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	10
0100001-4	8717365264207	0,5	4	H100-500KG-4m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	11,6
0100001-5	8717365264214	0,5	5	H100-500KG-5m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	13,2
0100001-6	8717365264221	0,5	6	H100-500KG-6m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	14,8
0100001-7	8717365090370	0,5	7	H100-500KG-7m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	16,4
0100001-8	8717365090387	0,5	8	H100-500KG-8m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	18
0100001-9	8717365089930	0,5	9	H100-500KG-9m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	19,6
0100001-10	8717365089947	0,5	10	H100-500KG-10m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	21,2
0100003-3	8717365264238	1	3	H100-1000KG-3m	6.3 x 19.1	5.0 x 23.6	1	303	26	303	160	69	91	160	30	43	22	13	13
0100003-6	8717365264269	1	6	H100-1000KG-6m	6.3 x 19.1	5.0 x 23.6	1	303	26	303	160	69	91	160	30	43	22	13	19
0100003-10	8717365089985	1	10	H100-1000KG-10m	6.3 x 19.1	5.0 x 23.6	1	303	26	303	160	69	91	160	30	43	22	13	27
0100005-3	8717365264276	1,6	3	H100-1600KG-3m	7.1 x 21.0	5.0 x 23.6	1	338	34	338	167,5	75	92,5	183	35	48	27	20	16
0100005-6	8717365264306	1,6	6	H100-1600KG-6m	7.1 x 21.0	5.0 x 23.6	1	338	34	338	167,5	75	92,5	183	35	48	27	20	22,6
0100007-3	8717365264313	2	3	H100-2000KG-3m	8.0 x 24.2	5.0 x 23.6	1	379	34	379	183	83	100	215	38	53	29	22	22
0100007-6	8717365264344	2	6	H100-2000KG-6m	8.0 x 24.2	5.0 x 23.6	1	379	34	379	183	83	100	215	38	53	29	22	29,2
0100009-3	8717365264351	3,1	3	H100-3100KG-3m	7.1 x 21.0	5.0 x 23.6	2	516	36	516	167,7	75	92,5	230	44	60	37	27	25
0100009-6	8717365264382	3,1	6	H100-3100KG-6m	7.1 x 21.0	5.0 x 23.6	2	516	36	516	167,7	75	92,5	230	44	60	37	27	35,2
0100011-3	8717365264399	5	3	H100-5000KG-3m	9.0 x 27.2	5.0 x 23.6	2	613	36	613	190	90	100	282	53	70	46	34	41
0100011-6	8717365264429	5	6	H100-5000KG-6m	9.0 x 27.2	5.0 x 23.6	2	613	36	613	190	90	100	282	53	70	46	34	54,5

Blueprint

